



HER301 THRU HER308

3.0 AMPS. HIGH EFFICIENCY RECTIFIERS

VOLTAGE RANGE

50 to 1000 Volts

CURRENT

3.0 Amperes


FEATURES

- * Low forward voltage drop
- * High current capability
- * High reliability
- * High surge current capability

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Lead: Axial leads, solderable per MIL - STD - 202, method 208 guaranteed
- * Polarity: Color band denotes cathode end
- * Mounting Position: Any
- * Weight: 1.18 grams

DO-201AD



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	HER 301	HER 302	HER 303	HER 304	HER 305	HER 306	HER 307	HER 308	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	300	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	210	280	420	560	700	V
Maximum D. C Blocking Voltage	V _{DC}	50	100	200	300	400	600	800	1000	V
Maximum Average Forward Rectified Current .375" (9.5mm) lead length @ T _A = 55°C (Note 1)	I _{F(AV)}	3.0								A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load(JEDEC method)	I _{FSM}	125								A
Maximum Instantaneous Forward Voltage at 3.0A (Note 1)	V _F	1.0				1.3	1.7			V
Maximum D. C Reverse Current @ T _A = 25°C at Rated D. C Blocking Voltage @ T _A = 100°C	I _R	10.0 200								μA μA
Maximum Reverse Recovery Time(Note 2)	T _{RR}	50					75			nS
Typical Junction Capacitance (Note 3)	C _J	80					50			pF
Operating Temperature Range	T _J	- 65 to + 125								°C
Storage Temperature Range	T _{STG}	- 65 to + 150								°C

NOTES: 1. Each Lead mounted on a $0.8 \times 0.8 \times 0.04$ " ($20 \times 20 \times 1$ mm) copper heat - sink.

2. Reverse Recovery Test Conditions: $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $I_{RR} = 0.25\text{A}$.

3. Measured at 1 MHz and applied reverse voltage of 4.0V D.C.

RATINGS AND CHARACTERISTIC CURVES (HER301 THRU HER308)

FIG. 1 - TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTICS




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL FORWARD CHARACTERISTICS




FIG. 5 - MAXIMUM NON - REPETITIVE FORWARD SURGE CURRENT





FIG. 6 - TYPICAL JUNCTION CAPACITANCE



This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.