

Lecturas normales de TV MITSUI Modelo: **MTV2006**

Fuente en Stb
B+ 90.2V

Fuente con Tv encendida
B+108.6V

Voltajes secundarios de fuente Stb

20.89V -----> B+ Vertical

11.46V

11.17V

Voltajes secundarios con Tv encendida

26.14V -----> B+ Vertical

13.78V

13.8V

Lecturas de Micro Jungla **8852CPNG6ER0**

Pin	Voltaje Stb	Voltaje On
1	0	2.7
2	0	0
3	5	5
4	0	0
5	5	5
6	2.26	2.3
7	2.15	2.1
8	0	0
9	5	5
10	0	0
11	0	0
12	0	1.14
13	0	1.8
14	0	6.5
15	0	4
16	0	4.9
17	.49	8.89
18	0	.28
19	.26	2.8
20	.26	2.9
21	.26	2.9
22	0	0
23	-.05	0
24	.49	2.5
25	0	3.56
26	.47	2.6
27	0	4.9
28	.49	3.49
29	0	8.88
30	0	4.57
31	0	1.8
32	0	4.3

Pin	Voltaje Stb	Voltaje On
33	0	2.95
34	0	2.5
35	.49	2.5
36	.5	5.1
37	0	2.1
38	0	4.31
39	0	2.1
40	0	0
41	.28	2.2
42	.2	2.2
43	.4	4.39
44	.5	5
45	.42	2.8
46	0	3.5
47	0	2.5
48	1.3	3.9
49	.49	8.89
50	0	2.5
51	0	2.4
52	0	2.8
53	0	0
54	0	0
55	5	5
56	5	0
57	5	5
58	5	5
59	2.19	1.9 Variando
60	5	5
61	2.20	1.9
62	1.36	4.3
63	5	5
64	0	3.3

Lecturas del IC **STV9302B** Vertical

Pin	Voltaje	Pin	Voltaje
1	3	5	13.58
2	24.9	6	25.53
3	1.8	7	3.05
4	0		

Lecturas IC **TDA7267A** Audio

Pin	Voltaje	Pin	voltaje
1	14.57	5	.12
2	0	6	0
3	.4	7	.1
4	0	8	.1