

## TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf	
Master cylinder x Reservoir	1.8	18	16 in.·lbf	
Master cylinder x Brake booster	13	130	9	
Brake line union nut	15	155	11	
Brake booster clevis lock nut	25	260	19	
Brake booster x Pedal bracket	13	130	9	
Brake booster push rod	7.4	75	65 in.·lbf	
Bleeder plug				
	Brake caliper	11	110	8
	Brake actuator	8.3	85	74 in.·lbf
Front disc brake caliper x Steering knuckle	118	1,200	87	
Front disc brake caliper x Flexible hose	39	400	29	
Rear disc brake torque plate x Rear axle carrier	104	1,065	77	
Rear disc brake caliper x Flexible hose	39	400	29	
Rear disc brake caliper installation bolt	34	350	25	
Parking brake pedal bracket x Body	13	130	9	
Parking brake pedal bracket x Parking brake pedal	32	330	24	
Parking brake release lever x Lower pad	5.4	55	48 in.·lbf	
Brake actuator x Actuator bracket	5.4	55	48 in.·lbf	
Actuator bracket x Body	19	195	14	
Front speed sensor installation bolt	7.8	80	69 in.·lbf	
Rear speed sensor installation bolt	7.8	80	69 in.·lbf	
Speed sensor harness clamp bolt	5.4	55	48 in.·lbf	