

# TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
Fuel line	for union bolt	29	300	21
	for flare nut	31	310	23
Fuel pump bracket x Fuel tank		5.5	55	48 in.·lbf
Fuel pump set plate x Fuel tank		3.0	30	26 in.·lbf
Fuel pressure regulator, Fuel filter x Fuel pump bracket		2.0	20	17 in.·lbf
Fuel inlet hose x Fuel tube	for SST	30	310	22
Delivery pipe x Intake manifold		18	185	13
Fuel pressure pulsation damper x delivery pipe		39	400	29
	for SST	33	340	24
VSV for EVAP x Intake manifold		18	185	13
Accelerator cable bracket x Intake manifold		18	185	13
LH front V-bank cover bracket x Engine hanger		7.5	80	66 in.·lbf
RH rear V-bank cover bracket x Engine hanger		7.5	80	66 in.·lbf
LH rear V-bank cover bracket x Intake manifold		7.5	80	66 in.·lbf
Fuel inlet pipe x Fuel tank	Bolt	3	30	26 in.·lbf
	Screw	1.5	15	13 in.·lbf
Fuel sender gauge x Fuel tank		3	30	26 in.·lbf
Fuel tank x Body		25	250	18
Fuel main tube x Fuel tank, Fuel filter		30	300	21
Fuel EVAP tube x Fuel tank		30	300	21
Throttle body x Intake manifold		18	185	13
Camshaft oil control valve x Front bearing cap		7.5	80	66 in.·lbf
Intake air control valve x Upper intake manifold		8.5	85	73 in.·lbf
Actuator x Upper intake manifold		8.5	85	73 in.·lbf
Upper intake manifold x Lower intake manifold		18	185	13
ECT sensor x Front water bypass joint		20	200	14
Knock sensor x Cylinder block		44	450	33
Heated oxygen sensor x Exhaust manifold, Front exhaust pipe		44	450	33